



Crewsaver®

SERVICE MANUAL

ERGOFIT 190 & 290

LIFEJACKETS

Crewsaver®

Survitec House, Lederle Lane, Gosport,
Hants. PO13 0FZ, England.
Tel: +44 (0) 1329 820000 Fax: +44 (0) 1329 236218
email: crewsaver@survitecgroup.com
Web: www.crewsaver.com

 **survitecgroup**

Service Bulletins and Amendments Register

No.	Description	Date
Issue 2	Page 4 - change in procedure for accessing manuals on the website.	April 2014
Issue 3	Manual expanded to include Ergofit 190N Pro and 290N EX References to Schrader Valves changed to UML PS Short Valves Reference to Venturi Vacuum System added (sections 6.1.2, 8.1.2 and Parts List) Back pressure testing of the operating head added	November 2016


Scope

This manual covers the servicing of the Ergofit 190N and 290N lifejackets without any current derivatives.

Index

Section 1		
	1.1	Introduction
	1.2	Product Description
	1.3	Data Sheet
	1.4	General Features
	1.5	Donning Instructions
Section 2		
	2.1	Service Station Guidelines
	2.2	On Receipt Inspection
	2.3	General Care
	2.4	Servicing Tools
	2.5	Service Record Sheet
	2.6	Servicing Tool Kit
Section 3		
	3	Unpacking the Lifejacket
Section 4		
	4	Cleaning & Laundering
Section 5		
	5	Inspection
Section 6		
	6	Testing
Section 7		
	7	Repairs
Section 8		
	8	Assembly & Repacking
Section 9		
	9	Replacement parts

1.1 Introduction

- 1.1.1. This Service Manual will be published on the Crewsaver website (www.crewsaver.com). Click on PARTNER AREA/LOGIN at the top of the screen. Personnel who have been trained in the servicing procedures for this lifejacket will be issued with a Username and Password to enable them to access the download section. Each manual carries an Issue Number and records of issue are logged by Crewsaver to ensure that the service network maintains correct and up to date servicing information. Emails will be sent regarding any new Issues. Periodically service bulletins may be issued which will be published on the Crewsaver website (www.crewsaver.com). Emails will also be sent. It is the service station's responsibility to regularly check the website for any new bulletins and to ensure inclusion within the servicing manual. The service bulletin register at the front of the Manual should be completed.
- 1.1.2. The information referenced in each section, follows a standard servicing procedure by which the inspection should take place.
- 1.1.3. This servicing manual details information to enable regular maintenance and servicing of the lifejacket to help prolong the life of the product and ensure it functions correctly.
- 1.1.4. The manual should be used as a reference document following training in servicing procedures instructed by Crewsaver personnel. The manual also details the equipment and parts needed for correct maintenance to be performed.
- 1.1.5. Servicing must be carried out annually at a service station authorised by the manufacturer. **1 yr** 
- 1.1.6. Regular servicing is to be carried out by qualified personnel trained by Crewsaver and holding a valid servicing certificate. Certificates are valid for a period of 3 years.

1.2 Product Description

- 1.2.1. The Ergofit 190N CS (Coastal), Ergofit 190N OS (Offshore) and Ergofit 190N Pro are single chamber Level 150 PFDs (Inflatable lifejackets).
- 1.2.2. The lifejackets are CE approved to BS EN ISO 12402-3.
- 1.2.3. The lifejackets are easy to don.
- 1.2.4. The buoyancy of the jackets is provided by a single chamber with an oral tube to ensure the full buoyancy can be achieved upon or after inflation.
- 1.2.5. The Ergofit 190N CS is inflated by either a Prosensor manual firing mechanism, a standard Prosensor automatic firing mechanism or a Hammar hydrostatic mechanism, and uses a 38 gr. CO₂ cylinder.
- 1.2.6. The Ergofit 190N OS and Ergofit 190N Pro are inflated by a standard Prosensor automatic firing mechanism or a Hammar hydrostatic mechanism, and use a 38 gr. CO₂ cylinder.
- 1.2.7. All versions come with an integral soft loop deck safety harness approved to ISO 12401 and EN1095. All versions have a zip closure system and in addition the CS version has a front zip.
- 1.2.8. The outer covers are made from a hard wearing black material.
- 1.2.9. All versions have permanently fitted dual crutch straps and dual lifting beackets.
- 1.2.10. The Ergofit 190 OS and Ergofit 190N Pro have a light and sprayhood fitted as standard (optional on CS version).

1.2 Product Description (Continued)

- 1.2.1. The Ergofit 290N OC (Ocean) and Ergofit 290N EX are single chamber Level 275 PFDs (Inflatable lifejackets).
- 1.2.2. The lifejackets are CE approved to BS EN ISO 12402-2.
- 1.2.3. The lifejackets are easy to don.
- 1.2.4. The buoyancy of the jackets is provided by a single chamber with an oral tube to ensure the full buoyancy can be achieved upon or after inflation.
- 1.2.5. Both versions are inflated by a standard Prosensor automatic firing mechanism or a Hammar hydrostatic mechanism, and use a 60 gr. CO₂ cylinder.
- 1.2.6. Both versions come with an integral soft loop deck safety harness approved to ISO 12401 and EN1095 and have a zip closure system.
- 1.2.7. The outer cover is made from a hard wearing black material.
- 1.2.8. Both lifejackets have permanently fitted dual crutch straps and dual lifting beackets. They also have a light and sprayhood fitted as standard.

1.3.1 Data Sheet

Features:	Ergofit 190N CS
Chamber Buoyancy:	190N
Buoyancy Category:	150N
Cover Colour	Black
MCA (UK) Approved	-
SOLAS Approved	-
CE Approved	X
Cylinder size	38g
Standard Prosensor Automatic	According to
Manual Prosensor	Customer
Hammar Automatic	Choice
Manual Override	X
Oral inflation tubes	X
Pressure relief valves	N/A
Hard wearing cover	X
Whistle - fitted	X
Retro-reflective tape	X
Dual Lifting Becket - fitted	X
Light - fitted	Optional
Spray Hood - fitted	Optional
Dual Thigh straps - fitted	X
Fall Arrest Harness	N/A
Closure method - Standard model	Zip

-

1.3.2 Data Sheet

Features:	Ergofit 190N Pro
Chamber Buoyancy:	190N
Buoyancy Category:	150N
Cover Colour	Black
MCA (UK) Approved	-
SOLAS Approved	-
CE Approved	X
Cylinder size	38g
Standard Prosensor Automatic	According to Customer
Hammar Automatic	Choice
Manual Override	X
Oral inflation tubes	X
Pressure relief valves	N/A
Hard wearing cover	X
Whistle - fitted	X
Retro-reflective tape	X
Dual Lifting Becket - fitted	X
Light - fitted	X
Spray Hood - fitted	X
Dual Thigh straps - fitted	X
Fall Arrest Harness	N/A
Closure method - Standard model	Zip


1.3.3 Data Sheet

Features:	Ergofit 190N OS
Chamber Buoyancy:	190N
Buoyancy Category:	150N
Cover Colour	Black
MCA (UK) Approved	-
SOLAS Approved	-
CE Approved	X
Cylinder size	38g
Standard Prosensor Automatic	According to Customer
Hammar Automatic	Choice
Manual Override	X
Oral inflation tubes	X
Pressure relief valves	N/A
Hard wearing cover	X
Whistle - fitted	X
Retro-reflective tape	X
Dual Lifting Becket - fitted	X
Light - fitted	X
Spray Hood - fitted	X
Dual Thigh straps - fitted	X
Fall Arrest Harness	N/A
Closure method - Standard model	Zip


1.3.4 Data Sheet

Features:	Ergofit 290N OC and EX
Chamber Buoyancy:	290N
Buoyancy Category:	275N
Cover Colour	Black
MCA (UK) Approved	-
SOLAS Approved	-
CE Approved	X
Cylinder size	60g
Standard Prosensor Automatic	According to
	Customer
Hammar Automatic	Choice
Manual Override	X
Oral inflation tubes	X
Pressure relief valves	N/A
Hard wearing cover	X
Whistle - fitted	X
Retro-reflective tape	X
Dual Lifting Becket - fitted	X
Light - fitted	X
Spray Hood - fitted	X
Dual Thigh straps - fitted	X
Fall Arrest Harness	N/A
Closure method - Standard model	Zip


1.4.1 General Features - Ergofit 190N CS






1.4.2 General Features - Ergofit 190N OS and Pro






1.4.3 General Features - Ergofit 290N OC and EX






1.5.1 Donning Instructions - Ergofit 190N CS



1.5.2 Donning Instructions - Ergofit 190N OS and Ergofit 290N OC



1.5.3 Donning Instructions - Ergofit 290N EX



2.1 Service Stations

- 2.1.1 Service stations shall comply with the following as a minimum;
 - 2.1.1.1 Servicing of Inflatable Lifejackets shall be carried out in a fully enclosed area only.
 - 2.1.1.2 The area shall be well lit and protected from direct sunlight
 - 2.1.1.3 The temperature and humidity shall be sufficiently controlled to ensure that the servicing of inflatable Lifejackets may be carried out successfully.
 - 2.1.1.4 The area shall be efficiently ventilated but free from draught
 - 2.1.1.5 Sufficient tools (including specialist tools) shall be available to ensure Lifejackets may be disassembled, tested and reassembled in accordance with this Manual. These shall include but not limited to:
 - 2.1.1.5.1 Manometers and pressure gauges
 - 2.1.1.5.2 Oil free and dry air supply
 - 2.1.1.5.3 Scales for weighing Gas Cylinders
 - 2.1.1.5.4 Crewsaver Service tool kit (See 2.6). This is recommended but similar calibrated devices may also be used.
 - 2.1.1.6 Stock of materials and components to allow efficient servicing with readily available replacement parts to ensure a prompt service for the customer.
 - 2.1.1.7 Only personnel trained and certified in accordance with Crewsaver requirements are approved to carry out Servicing and Maintenance. They must be holders of a valid Certificate issued by Crewsaver.
 - 2.1.1.8 The service station shall be of an approved standard.
 - 2.1.1.9 Procedures shall be introduced to ensure that service bulletins, Manuals and replacement parts are obtained from Crewsaver.
 - 2.1.1.10 Subsequent to initial approval and thereafter the service station shall be subject to regular surveillance by Crewsaver.
 - 2.1.1.11 The service station must comply and have met all QA criteria in the Crewsaver servicing protocol file.

2.2 On Receipt Inspection

- 2.2.1 On receipt of the Lifejacket(s), check the state of the packaging before opening and notify the owner and the company delivering the package of any defects or damage.
- 2.2.2 On opening the package, check the contents for their general condition and quantity.
- 2.2.3 Prepare Servicing Record Sheet.
- 2.2.4 Visually inspect the cover and inflation chamber for damage, abrasion, contamination etc. in accordance with this manual.
- 2.2.5 Note replacements required on the record sheet.
- 2.2.6 Unless obvious damage is evident, test the Lifejacket in accordance with Section 6. If it is considered that the damage found would cause the Lifejacket to fail the tests then corrective action shall be carried out prior to testing.
- 2.2.7 Damaged areas shall be marked using wax based crayon only. Marks shall be made with a small circle or cross. Ballpoint, rollerball or other forms of ink shall not be used. If in doubt refer to Crewsaver for guidance.
- 2.2.8 Repairs to the outer cover and the webbing are not permitted.
- 2.2.9 Repairs to welded components including the inflation chamber are expressly forbidden.

2.3 General Care

- 2.3.1 The Lifejacket should be stowed in accordance with the manufacturer's instructions
- 2.3.1.1 Lifejackets should be stowed in a dry compartment. Avoid high humidity, such as a car boot.
 - 2.3.1.2 Lifejackets should have stowage facilities which are provided with a method to encourage moisture removal.
 - 2.3.1.3 Lifejackets should be stowed vertically, for example hung on hooks, in order that any trapped water or condensation can drain away naturally.
 - 2.3.1.4 Lifejackets should be rinsed in fresh water and dried thoroughly after use.

WARNING

Prior to sponging or washing remove automatic capsules from the firing mechanism. Allow to dry thoroughly afterwards.

- 2.3.2 Contaminants such as oil or diesel fuel may be sponged off immediately with clean water and allowed to dry naturally.
- 2.3.3 Mud can be removed with a stiff (not wire) brush when dry.
- 2.3.4 The outer cover may be hand washed in good quality mild detergent in cool water (40°C). Rinse well, drip dry naturally in air.
- 2.3.5 Sponge the inflation chamber with pure soap solution only. Rinse in clean water immediately, inflate and allow to dry naturally in air.

WARNING

Do not use proprietary cleaning fluids, thinners, spirits or similar substances.

- 2.3.6 In cases of severe contamination the unit shall be deemed beyond economic repair and the customer advised to purchase a replacement lifejacket.

WARNING

Make sure you know how to use and fit this Lifejacket before an emergency occurs.
Always try and inflate the Lifejacket in the water. If already inflated, cross arms over the chest before jumping.

- 2.3.7 It is advised that personnel are familiarised with the operation of all Lifejackets and lifesaving appliances.

2.4 Lifejacket Servicing Tools

Fig. 2.4 Table of Tools Required

Description	Type
Crewsaver Servicing Tool Kit A fine screw driver or tool suitable for removing gaskets Boning tool Roller Brushes Scissors or good quality trimming shears “Chinagraph” pencil Tailors chalk Fine point indelible pen 1 off metal calibrated metre stick Scales to weigh gas cylinders Adaptor/tee piece for testing inflation chambers. Manometer Timing Device Thermometer Clean and dry air supply 1 off ball pein hammer 450mm wide bag sealer (3mm element) Crewsaver Venturi Vacuum System Back pressure test unit	0-1000gram (+1/-1 grams) 0-500Mbar 0-40°C
Suitable large surface area for the work to be carried out 1 off FR steel cabinet (adhesive store) 1 off HD industrial sewing machine (e.g. Singer 96K, Juki, Durkopp etc.)	
<p><i>N.B. In case of difficulty contact Crewsaver direct (Not sewing machines, cabinets or tables - these parts may be sourced locally).</i></p>	

2.5 Lifejacket Service Record Sheet

- 2.5.1. An electronic copy of the sheet is available to aid reproduction (or copy next page).
- 2.5.2. Each lifejacket serviced should be recorded either individually or as a batch, showing the serial numbers and the work performed during the service.
- 2.5.3. The service record sheet should be signed and a copy given to the owner certifying that the lifejacket has been serviced.
- 2.5.4. All replacement parts should be noted - recording either the serial numbers of the component or the expiry date.
- 2.5.5. The record sheet shown on the next page is a recommended version. Similar record sheets, including the same information, may also be used.



Crewsaver®

CERTIFICATE NUMBER:

W/O Number:

LIFEJACKET SERVICING SCHEDULE

TYPE	
CUSTOMER	
VESSEL	
LAST SERVICED BY	DATE OF LAST SERVICE

SERIAL NUMBER/S:

CHAMBER INSPECTION	<input type="checkbox"/> <input type="checkbox"/>	COMMENTS
GENERAL CONDITION		
MATERIAL		
WELDS		
WEBBINGS		
RETRO TAPE		
WHISTLE		
ORAL TUBES		
RELIEF VALVES		
MANIFOLDS		
UML PS Short Valves		
CYLINDERS		
LIGHT		
CYALUME POCKET		
BUDDY LINE		

INFLATION MECHANISM	<input type="checkbox"/> <input type="checkbox"/>	COMMENTS
OPERATING MECHANISM		
CORD		
AUTOMATIC CAPSULE		
WASHERS		
RETAINING NUT		
RETAINING CLIP		
TOGGLE		

SPRAY HOOD	<input type="checkbox"/> <input type="checkbox"/>	COMMENTS
FABRIC		
ATTACHMENT		
VELCRO		

WEBBINGS	<input type="checkbox"/> <input type="checkbox"/>	COMMENTS
WAIST BELT / HARNESS		
BACK STRAP		
LIFTING BECKET		
CROTCH STRAP		
BUCKLES		
STITCHING		

COVER	<input type="checkbox"/> <input type="checkbox"/>	COMMENTS
MATERIAL		
VELCRO		
ZIP		
PLB POCKETS		

PRESSURE TEST RESULTS

TIME		FRONT CHAMBER	REAR CHAMBER
ON			
OFF			
TEMP.		ON	OFF

RELIEF VALVE TEST RESULTS

	FRONT CHAMBER	REAR CHAMBER
OPEN		
CLOSE		

REPAIRED ITEMS (COMMENTS)

SERVICED BY:

DATE:

2.6 Lifejacket Servicing Tool Kit



Cylinder Torque Strap




UML Mk5 Auto Socket



Manometer



Valve Extraction Tool



Turned Socket



Inflation Adaptor



Pressure Measuring Adaptor



Calibrated Socket Driver (Tighten Cylinder)



Calibrated Socket Driver (Remove & Replace Locking Nuts For UML & HR)



Calibrated Torque Driver (Schraeder Valve)

3.1 Unpacking

- 3.1.1 Pull the zips apart exposing the operating head and cylinder. Care should be taken not to snag the firing line.

WARNING: All defects should be noted onto the service record sheet.

- 3.1.2.1 Following unpacking refer to:

a.) Manual Operation: Fig 3.2 - United Moulders Prosensor Manual head

b.) Automatic Operation: Fig 3.3 - United Moulders Prosensor Automatic head.

- 3.1.2.1.1 Automatic Only. Unscrew the Automatic Capsule if fitted from the operating mechanism. Place to one side for testing and reassembly later. See Section 6 for details.

- 3.1.2.1.2 Carefully remove the inflation cylinder by unscrewing it from the operating mechanism. Retain for further Inspection. Refer to Section 5.

- 3.1.2.1.3 Remove Operating Mechanisms by unscrewing the retaining screw on the top of the inflation mechanism. Retain for further Inspection. Refer to Section 5.

- 3.1.2.2 If a Hammar operating mechanism is fitted, remove using the special Hammar operating head "Service Key". See Fig 3.5. Place to one side for further inspection. Refer to Section 5.

- 3.1.3. Remove light and battery if fitted and if required. Place to one side for further inspection. Refer to section 5.
- 3.1.4. For Cleaning. Refer to Section 4.
- 3.1.5. Carry out visual inspection. Refer to section 5.

Fig 3.2 Unpacking the Ergofit (all versions)

1. Open the velcro tab.

2. Pull apart the zip, opening the zip via the quick burst elements, holding the cover either side.

3. Once the zip has opened insert your finger and slide it around the lifejacket.

Undo the zip all the way around the outside of the lifejacket. The lifejacket cover should now be open and the inflation chamber visible.

Fully separate the zip. Both sides of the zip should be apart, with the zip slider free to move back around the lifejacket to the start.






Fig 3.3 UML Prosensor Manual Operating Head

- 1 Unscrew the CO₂ cylinder from the manual firing head. Once the cylinder has been removed inspect the cylinder sealing O-Ring . Check the seal is in place and that it is in a good condition. Check to see if the cylinder has been used. This should be performed by check weighing. If under the min. weight as displayed on the cylinder body, discard in a safe manner.
- 2 Unscrew the retaining screw from the top of the firing head, using torque screwdriver. Check for corrosion and discard if corroded. Inspect the top sealing O-ring. This must be replaced with a new part if damaged.
- 3 Remove the operating head from the manifold which is welded to the inflator fabric. Inspect the bottom sealing O-ring. This must be replaced with a new part if damaged.
- 4 Check the pull cord and handle for fraying or damage.


Fig 3.4 United Moulders Prosensor Automatic Head



- 1 Unscrew the Automatic firing capsule from the end of the operating head. This should only be done after the test detailed in Section 6 has been performed in order to test the old unit, or if the operating head has already been fired. Discard and replace with a new automatic firing capsule upon reassembly. The Capsule must be replaced if it expires before the date of the next annual service.
- 2 Unscrew the CO₂ cylinder from the automatic operating head. Once the cylinder has been removed inspect the cylinder sealing O-Ring . Check the seal is in place and that it is in a good condition. Take the cylinder and check to see if the cylinder has been used. This should be performed by check weighing. If under the minimum weight as displayed on the cylinder body, discard in a safe manner.
- 3 Unscrew the retaining screw from the top of the firing head, using torque screwdriver. Check for corrosion and discard if corroded. Inspect the top sealing O-ring. This must be replaced with a new part if damaged.
- 4 Remove the operating head from the manifold which is welded to the inflation chamber fabric. Inspect the bottom sealing O-ring. This must be replaced with a new part if damaged.
- 5 Check the pull cord and handle for fraying or damage.



Fig 3.5 Hammar Operating Head

Fig. 3.5.1





1.
Place the lifejacket on a smooth, flat surface and wipe off any water. Hold the gas cylinder through the fabric, using one hand.

Fig. 3.5.2




2.
Insert metal key as shown in 2a and turn the key counter-clockwise (2b) between black locking ring and labelled yellow cap. The black locking ring will now turn counter-clockwise.

Fig. 3.5.3



3.
Now turn black locking ring counter-clockwise (3a) and lift cap (3b). (cap = yellow inflator operating head) Dispose of used cap.

Fig. 3.5.4



4.
Squeeze sealing ring to elongate and remove the inflator body and CO₂ cylinder through the sealing ring. Dispose of used inflator body and cylinder in an environmentally approved manner.

4.1 Cleaning Lifejackets

- 4.1.1 The current standard cover of the Ergofit can be cleaned with care. In the event that contamination is such that the materials are inherently damaged refer to section 7.
- 4.1.2 For all types of cover, mud can be removed with clean water and the zip can be cleaned with a stiff (not wire) brush when dry.
 - 4.1.2.1 Contaminants such as oil or diesel fuel may be sponged off immediately with clean water and allowed to dry naturally.
 - 4.1.2.2 Mud can be removed with a stiff (not wire) brush when dry.
 - 4.1.2.3 Covers may be hand washed in good quality mild detergent in cool water (40 °C). Rinse well, air drip dry.
- 4.1.3 Sponge the inflation chamber with PURE SOAP SOLUTION ONLY. Rinse in clean water immediately, inflate and air dry.

WARNING: Do not use proprietary cleaning fluids, thinners, spirits or similar substances.

5.1 Outer Cover Inspection


- 5.1.1 Visually inspect the cover material for wear, abrasion, pulled threads, contamination, cuts and holes.
 - 5.1.2 Carefully examine the zips and the slider for wear, broken teeth or slider and worn or fraying tape.
 - 5.1.2 If necessary the cover may be washed. Refer to Section 4.
 - 5.1.3 Repairs to the outer cover are not permitted.
 - 5.1.4 If it is considered that the cover is so badly damaged that the lifejacket is no longer serviceable, the customer shall be advised and offered a replacement lifejacket.
- NOTE: Due to the construction of this lifejacket no individual cover is available for replacement, therefore the lifejacket as a whole must be replaced.

5.2 Inflation Chamber Inspection

- 5.2.1 Visually inspect the inflation chamber material for wear, pulled threads, contamination or signs of mistreatment.
- 5.2.2 Visually inspect all welds.
- 5.2.3 Visually inspect all webbings in accordance with Section 5.6
- 5.2.4 Visually inspect the whistle and its attachment to the lifejacket for mistreatment, defects, and fraying of the cord and its attachment.
- 5.2.5 Test Lifejacket in accordance with Section 6.

5.3 Gas Cylinders

- 5.3.1 Visually examine:
 - 5.3.1.1. For Corrosion (All cylinders corroded with red rust or with visible pitting must be replaced).
 - 5.3.1.2. Pierced or damaged piercing disc.
 - 5.3.1.3. That the cylinder has the correct gas charge - 38gm (Ergofit 190N) or 60 gm (Ergofit 290N)
- 5.3.2 Check Min Weight of Cylinder against that marked on the barrel. If the lifejacket is fitted with a Hammar Inflation system (either A1 or MA1) the cylinder will be glued into the Hammar backplate. Do NOT attempt to unscrew the cylinder from the backplate. Instead add 22 grams to the minimum weight shown on the cylinder.



Remedial Action: If any of the above conditions are found to be incorrect the cylinder shall be replaced. See Section 9.

5.4 Mouth Inflation Valve

- 5.4.1 Visually inspect for damage.
- 5.4.2 Test in accordance with Section 6.

Remedial Action: These items are not repairable. Refer to Section 9 for replacement part.

5.5 Inflation System

- 5.5.1 Visually inspect the Operation of the Manual or Automatic Mechanism for:
 - 5.5.1.1 Operation of the Manual override lever. This shall move easily and freely.
 - 5.5.1.2 Operation of the firing pin cam action. Similarly this shall be a smooth action when the lever is operated.
 - 5.5.1.3 Firing Pin centre discharge hole clear.
 - 5.5.1.4 Activation cord for fraying and damage.
 - 5.5.1.5 Moulded body for cracks and damage. Special attention to be given to the areas around the operating lever/body connection pin.
 - 5.5.1.6 Check the Automatic plunger (Automatic Head Only) at the base of the unit when depressed moves the firing pin and that the plunger and the firing pin return to their original positions when released.
 - 5.5.1.7 Check that the indicator panels show red when the cylinder and automatic capsule are removed and show green when the cylinder and capsule are replaced.

Remedial Action: In the event that the Operating Mechanism fails any of the above inspection procedures, the complete unit shall be replaced. No Repairs are allowed. Refer to Section 9 for the part number of the relevant replacement part.

- 5.5.2 Visually inspect the Operation of the Automatic Capsule on the automatic Operating Head:
 - 5.5.2.1 Check plug is in place at the base of the capsule.
 - 5.5.2.2 New Capsules are to be fitted where the expiry date is before the next annual service of the lifejacket. Current capsules are marked with the month and year of expiry. Earlier capsules marked with year of expiry only expire at the end of that year.
 - 5.5.2.2.1 If the capsule is to be replaced – Re-fit the old capsule and carry out operational tests. Refer to section 6.
- 5.5.3 For Hammar Hydrostatic systems, remove and inspect. For the Hydrostatically operated head ensure that indicator is green, and that the handle has not been pulled, or displaced.

5.6 Webbings

- 5.6.1 Visually inspect for damage:
 - 5.6.1.1. Fraying
 - 5.6.1.2. Pulled Threads
 - 5.6.1.3. Broken Stitches

Remedial Action: No repairs are allowed. In the case of damage being found, return the Lifejacket to Crewsaver.

5.7 Buckles

- 5.7.1 Visually inspect all buckles used on the webbings for signs of damage or corrosion.

Remedial Action: No repairs are allowed. In the case of damage being found, return the Lifejacket to Crewsaver.

5.8 Labelling/Markings

- 5.8.1. Check all Markings and Labelling are clear and legible.

Remedial Action: No repairs are allowed. In the case of damage being found, return the Lifejacket to Crewsaver.


5.9 Lights (if fitted)

- 5.9.1 Some models are fitted with the Crewsaver CSL Water Activated Light.


Visually inspect the light for signs of damage to:

- 5.9.1.1. The switch.
- 5.9.1.2. the cable.
- 5.9.1.3. the lens and its mounting or housing.


- 5.9.2 Check expiry date on battery. The expiry date must exceed the date of the next annual service. If the light has expired or expires before the next service then it must be replaced. (See Section 9).



- 5.9.3 Ensure that the switch is in the Auto-on position.



Water activated switch in Auto-on position (Earlier models)



Water activated switch in Auto-on position (Later models)

- 5.9.4 Test the assembly as detailed in Section 6

6.1 Inflation Chamber

6.1.1. Air Holding Test.

- 6.1.1.1 Connect through a suitable Tee piece and adaptor, the oral tube with the oral valve in the open position, to a graduated water manometer (or a similar digital device for measuring back pressure).
- 6.1.1.2 Slowly inflate the lifejacket from a regulated supply until manometer reads 200mbar

Warning: Regulated supply pressure must not exceed 20psi.

- 6.1.1.3 Close off the air supply and leave for 10 minutes to ensure pressure is stable.
- 6.1.1.4 Check and record the pressure and temperature reading on the Service Record Sheet.
- 6.1.1.5 Leave for 30 minutes.
- 6.1.1.6 Check and record the pressure and temperature reading on the Service Record Sheet.

The maximum difference in the two pressure readings (pressure drop) allowed is 10%. The temperature differential shall be within plus or minus 3 degrees of the original reading. For each degree Centigrade rise in temperature subtract 2.5 mbar. For each degree Centigrade drop in temperature add 2.5 mbar to the readings to obtain the actual pressure variation. Should the temperature variation be outside 3 degrees either way then the test shall be repeated.

PSI	in/H ₂ O	in/Hg	mm/H ₂ O	mm/Hg	kg/cm ²	bar	mbar	Pa	kPa
1.0	27.71	2.036	703.1	51.75	0.0703	0.0689	68.95	6895	6.895
1.1	30.48	2.240	773.4	56.93	0.0773	0.0758	75.85	7585	7.585
1.2	33.25	2.443	843.7	62.10	0.0844	0.0827	82.74	8274	8.274
1.3	36.02	2.647	914.0	67.28	0.0914	0.0896	89.64	8964	8.964
1.4	38.79	2.850	984.3	72.45	0.0984	0.0965	96.53	9653	9.653
1.5	41.57	3.054	1054.7	77.63	0.1055	0.1034	103.43	10343	10.34
1.6	44.34	3.258	1125.0	82.80	0.1125	0.1102	110.32	11032	11.03
1.7	47.11	3.461	1195.3	87.98	0.1195	0.1171	117.22	11722	11.72
1.8	49.88	3.665	1265.6	93.15	0.1265	0.1240	124.11	12411	12.41
1.9	52.65	3.868	1335.9	98.33	0.1336	0.1309	131.01	13101	13.10
2.0	55.42	4.072	1406.2	103.50	0.1406	0.1378	137.90	13790	13.79
2.1	58.19	4.276	1476.5	108.68	0.1476	0.1447	144.80	14480	14.48
2.2	60.96	4.479	1546.8	113.85	0.1547	0.1516	151.69	15169	15.17
2.3	63.73	4.683	1617.1	119.03	0.1617	0.1585	158.59	15859	15.86
2.4	66.50	4.886	1687.4	124.20	0.1687	0.1654	165.48	16548	16.55
2.5	69.28	5.090	1757.8	129.38	0.1758	0.1723	172.38	17238	17.24
2.6	72.05	5.294	1828.1	134.55	0.1828	0.1791	179.27	17927	17.93
2.7	74.82	5.497	1898.4	139.73	0.1898	0.1860	186.17	18617	18.62
2.8	77.59	5.701	1968.7	144.90	0.1968	0.1929	193.06	19306	19.31
2.9	80.36	5.904	2039.0	150.08	0.2039	0.1998	199.96	19996	20.00
3.0	83.13	6.108	2109.3	155.25	0.2109	0.2067	206.85	20685	20.69
3.1	85.90	6.312	2179.6	160.43	0.2179	0.2136	213.75	21375	21.37
3.2	88.67	6.515	2249.9	165.60	0.2250	0.2205	220.64	22064	22.06
3.3	91.44	6.719	2320.2	170.78	0.2320	0.2274	227.54	22754	22.75
3.4	94.21	6.922	2390.5	175.95	0.2390	0.2343	234.43	23443	23.44
3.5	96.99	7.126	2460.9	181.13	0.2461	0.2412	241.33	24133	24.13
3.6	99.76	7.330	2531.2	186.30	0.2531	0.2480	248.22	24822	24.82
3.7	102.53	7.533	2601.5	191.48	0.2601	0.2549	255.12	25512	25.51
3.8	105.30	7.737	2671.8	196.65	0.2671	0.2618	262.01	26201	26.20
3.9	108.07	7.940	2742.1	201.83	0.2742	0.2687	268.91	26891	26.89
4.0	110.84	8.144	2812.4	207.00	0.2812	0.2756	275.80	27580	27.58
4.1	113.61	8.348	2882.7	212.18	0.2882	0.2825	282.70	28270	28.27
4.2	116.38	8.551	2953.0	217.35	0.2953	0.2894	289.59	28959	28.96
4.3	119.15	8.755	3023.3	222.53	0.3023	0.2963	296.49	29649	29.65
4.4	121.92	8.958	3093.6	227.70	0.3093	0.3032	303.38	30338	30.34
4.5	124.70	9.162	3164.0	232.88	0.3164	0.3101	310.28	31028	31.03
4.6	127.47	9.366	3234.3	238.05	0.3234	0.3169	317.17	31717	31.72
4.7	130.24	9.569	3304.6	243.23	0.3304	0.3238	324.07	32407	32.41
4.8	133.01	9.773	3374.9	248.40	0.3374	0.3307	330.96	33096	33.10
4.9	135.78	9.976	3445.2	253.58	0.3445	0.3376	337.86	33786	33.79
5.0	138.55	10.180	3515.5	258.75	0.3515	0.3445	344.75	34475	34.48
5.1	141.32	10.384	3585.8	263.93	0.3585	0.3514	351.65	35165	35.17
5.2	144.09	10.587	3656.1	269.10	0.3656	0.3583	358.54	35854	35.86
5.3	146.86	10.791	3726.4	274.28	0.3726	0.3652	365.44	36544	36.55
5.4	149.63	10.994	3796.7	279.45	0.3796	0.3721	372.33	37233	37.24
5.5	152.41	11.198	3867.1	284.63	0.3867	0.3790	379.23	37923	37.93
5.6	155.18	11.402	3937.4	289.80	0.3937	0.3858	386.12	38612	38.62
5.7	157.95	11.605	4007.7	294.98	0.4007	0.3927	393.02	39302	39.31
5.8	160.72	11.809	4078.0	300.15	0.4077	0.3996	399.91	39991	39.99
5.9	163.49	12.012	4148.3	305.33	0.4148	0.4065	406.81	40681	40.68
6.0	166.26	12.216	4218.6	310.50	0.4218	0.4134	413.70	41370	41.37

6.1.1.7. If Lifejacket fails the Air holding test inspect as follows.

6.1.1.7.1 With the lifejacket inflated carefully brush or spray the surface with a weak solution of soap and water or alternatively lower the lifejacket into a tank of water to observe for bubbles.

6.1.1.7.2 Identify and mark the source of leakage. Wash off in clean water and allow to dry naturally in air.

6.1.1.7.2.1 Special Attention to be given to:

a) Manifold UML PS Short Core

b) Oral Tube/ Top-up Valve

6.1.2 If the test is satisfactory deflate the Lifejacket in preparation for re-assembly. Refer to Section 8.

6.1.2.1. Insert the inverted oral valve dust cap into the top of the oral valve and expel the air. Lifejackets may also be deflated using the Venturi Vacuum System. For the part number, refer to Section 9.

6.1.3 Subsequent to remedial action being taken (see Section 7), retest the lifejacket in accordance with Section 6.

6.2 Valves

6.2.1. Oral Valve.

6.2.1.1. When removing the test adapter from each oral valve check that the oral valve reseats. If in doubt this may be checked by placing the valve underwater.

6.2.2 UML PS Short Valve.

6.2.2.1 Should a leak be found in the UML PS Short valve the faulty core must be removed and a new valve inserted using the Torque screwdriver from the tool kit.

6.3 Inflation Mechanisms

6.3.1 Operational Test for United Moulders Automatic Operating Heads (to be performed when capsules have expired).

6.3.1.1 Remove the operating mechanism from the lifejacket and remove the cylinder.

6.3.1.2 Assemble the expired capsule onto the body of the operating mechanism.

6.3.1.3 Place the complete unit into water and check that the unit operates within 5 seconds.

6.3.1.4 If the mechanism fails to pass this test replace the complete unit. Refer to Section 9 for part Number of the replacement part.

NOTE: all failures of this test must be reported to Crewsaver. Crewsaver may require the failed units to be returned, please do not discard.

6.4 Lights

6.4.1. Crewsaver CSL Water Activated Light.

Test the light by immersing the sensor in water. The light must flash, remove the light from the water and dry it. The light must stop flashing. If the light does not flash the unit has expired and must be replaced.

All light units used have a detailed expiry date, after which the light should be carefully disposed of.

6.5 Retro Reflective Tape

6.5.1 If the retro reflective tape shows any signs of degradation the following tests shall be carried out in accordance with Marine Guidance Note MGN 105 (M+F) Issued by the UK Marine and Coast guard Agency March 1999.

6.5.1.1 Place a new piece of the same retro-reflective material to, and on the same plane as, a representative piece of material fitted to the appliance.

6.5.1.2 Pour water over both pieces of material.

6.5.1.3 Using a powerful torch or "Aldis" lamp held at eye level, compare the performance of the two pieces of material from a distance of 10 Metres.

6.5.1.4 If a noticeable deterioration in performance is observed then the retro-reflective material on the appliance should be replaced.

6.5.1.5 Dry off the lifejacket before repacking.

7.1 Outer Cover

7.1.1 No repairs are permitted to the outer cover.

7.2 Inflation Chamber

7.2.1 No repairs are permitted to the inflator fabric or its assembly, due to the construction of this lifejacket.

7.2.2 Components attached to the inflator may be repaired in line with the limits defined below.

7.3 Gas Cylinders

7.3.1 No repairs permitted. For the Part No. of the replacement part refer to Section 9

7.3.2 Please ensure cylinders are disposed of in accordance with local regulations.

Treat empty cylinders as steel for recycling purposes.

7.4 Valves


7.4.1 No repairs permitted. For the Part No. of the replacement parts refer to Section 9

7.4.2 Replacement of the Oral valve may be achieved by.

7.4.2.1 Carefully removing the defective unit by applying force, with a blunt instrument, behind the oral valve Squeezing the tube and gently pushing the valve out.

7.4.2.2 Push the replacement valve into the oral tube.

Fig. 7.4



7.5 Inflation System

7.5.1 A UML PS Short core is located inside the Valve Stem.

7.5.1.1 Remove and replace using the calibrated torque driver for UML PS Short valves set to 0.32 - 0.36 Nm. Refer to Section 9 for the Part No. of the replacement part.

WARNING: Only fit replacement UML PS Short valves obtained from Crewsaver.

7.5.2 Operating Mechanism.

7.5.2.1 No repairs permissible. Replace the complete unit.
Refer to Section 9 for the Part No. of the replacement part.

7.6 Webbings

7.6.1 No repairs are permitted to the webbing on the lifejacket. Lifejackets with damaged webbing (including crutch straps) should be returned to Crewsaver.

7.7 Buckles

7.7.1. These components are not repairable or replaceable. Lifejackets with damaged buckles should be returned to Crewsaver.

8.1 Assembly

- 8.1.1 Ensure the whistle is positioned and tied in correctly.
- 8.1.2 Expel the air from the chamber by inverting the dust cap on the oral tube. Lifejackets may also be deflated using the Crewsaver Venturi Vacuum System. For the part number, refer to Section 9.
- 8.1.3 Assemble the Operating Mechanism to the inflator.
 - 8.1.3.1 For Halkey Roberts Manual Operating Mechanisms. See Fig 8.2
 - 8.1.3.1.1 A new firing retaining pin/ clip, upper and lower manifold gaskets must be fitted. Refer to Section 9 for Part Numbers.
 - 8.1.3.1.2 Fit new lower gasket.
 - 8.1.3.1.3 Locate operating head onto manifold.
 - 8.1.3.1.4 Fit new top gasket.
 - 8.1.3.1.5 Tighten the retaining nut onto the body using the Calibrated torque driver provided in the Crewsaver servicing tools. Note: Retaining nut must be tightened to between 2.5 and 2.7 Nm.
 - 8.1.3.1.6 Firmly screw the cylinder adaptor by hand into the head
 - 8.1.3.1.7 Connect the cylinder adaptor to the pressure test unit
 - 8.1.3.1.8 Pressurise the head to between 25 and 30 psi and release the control to its vertical position.
 - 8.1.3.1.9 There may be a slight decrease in pressure over the first 2 seconds as the unit stabilises. Leave for 10 seconds and check for any further decrease in pressure shown on the gauge
 - 8.1.3.1.10 Release the pressure by turning the control to deflate.
 - 8.1.3.1.11 If there had been any decrease in pressure remove the cylinder adaptor, remove the operating head and check the following.
 - a. Thick and thin washer either side of the head.
 - b. Damage to the D post seating.
 - c. Cross thread chrome nut
 - d. The cylinder seating washer.
 - e. The schrader or pang valve in the 'D' post.
 - f. The operating head
 - 8.1.3.1.12 Fit the gas cylinder to the firing mechanism by hand then check using the torque wrench (4Nm) and head adaptor from the tool kit. The operating head is gripped in one hand and the cylinder tightened using the torque wrench with the cylinder tightening tool held in the other hand.

Warning: Care must be taken not to 'cross thread' the connection.

- 8.1.3.2 For United Moulders Mk5 Automatic Operating Mechanisms. See Fig 8.3
 - 8.1.3.2.1 A new retaining clip must be fitted. Refer to Section 9 for replacement parts.
 - 8.1.3.2.2 Fit the new automatic firing capsule to the operating head, screw hand tight.
 - 8.1.3.2.3 Locate Operating head onto the Manifold.
 - 8.1.3.2.4 Tighten the retaining nut onto the body using the Calibrated torque driver provided in the Crewsaver servicing tools. Note: Retaining nut must be tightened to between 2.5 and 2.7 Nm.
 - 8.1.3.2.5 Firmly screw the cylinder adaptor by hand into the head
 - 8.1.3.2.6 Connect the cylinder adaptor to the pressure test unit
 - 8.1.3.2.6 Pressurise the head to between 25 and 30 psi and release the control to its vertical position.
 - 8.1.3.2.7 There may be a slight decrease in pressure over the first 2 seconds as the unit stabilises. Leave for 10 seconds and check for any further decrease in pressure shown on the gauge
 - 8.1.3.2.8 Release the pressure by turning the control to deflate.
 - 8.1.3.2.9 If there had been any decrease in pressure remove the cylinder adaptor, remove the operating head and check the following.
 - a. Thick and thin washer either side of the head.
 - b. Damage to the D post seating.
 - c. Cross thread chrome nut
 - d. The cylinder seating washer.
 - e. The schrader or pang valve in the 'D' post.
 - f. The operating head

Warning: Care must be taken not to 'cross thread' the connection.

8.1 Assembly

8.1.3.1.12 Fit the gas cylinder to the firing mechanism by hand then check using the torque wrench (4Nm) and head adaptor from the tool kit. The operating head is gripped in one hand and the cylinder tightened using the torque wrench with the cylinder tightening tool held in the other hand.

8.1.3.3 For Hammar Hydrostatic and Manual Operating Mechanisms. See Fig 8.4

8.1.3.3.1 If the operating head has been fired, tampered with, does not comply with any of the details in 5.5.3 or the red firing handle is missing; a replacement operating mechanism must be fitted.

8.1.3.3.2 If a new CO₂ cylinder is required a replacement cylinder ALREADY ATTACHED to an inflator body must be purchased from Crewsaver.

8.1.3.3.3 Insert the cylinder and inflator body into the inflation chamber through the sealing ring, ensure that the cylinder is vertically positioned in the inflation chamber.

8.1.3.3.4 Seat the inflator body underneath the sealing ring. Locate the inflation mechanism to the sealing ring and the inflator body, with the red firing handle facing directly down the inflation chamber away from the cylinder. Using the Hammar operating head tightening key, clip the mechanism closed.

Warning: Care must be taken not to 'cross thread' the connection.


8.1.4 To re-pack the lifejacket see Fig 8.5 (Crewfit 290 Standard), Fig 8.6 (Crewfit 290 Hammar) or Fig 8.7 (Crewfit 290 Fire Resistant).

8.1.5 Expel additional excess air, during the packing operation, from within the inflator by again inverting the cap on the oral tube and inserting it into the oral valve. When all excess has been expelled replace the cap.

8.1.6 Mark Service Label on Lifejacket (using an indelible pen) and Service Record Sheet with the date of the service.


8.1.7 Ensure the serial number has been correctly recorded and that it is clearly marked on the Record Sheet.

Warning: The lifejacket folding procedures must be followed accurately to ensure that the lifejacket inflation mechanism operates and the lifejacket deploys correctly. The lifejacket shall not be folded and/or packed using any other method or procedure than that specified.

Fig 8.2 UML ProSensor Manual Operating Head

- 1 Check that the cylinder sealing O-Ring in the end of the operating head has been correctly fitted, or replaced if necessary. Ensure that the cylinder has been check weighed before fitting to the lifejacket. Fit the gas cylinder to the firing mechanism using the torque wrench (4Nm) and head adaptor from the tool kit. The cylinder is gripped in one hand and the head tightened using the torque wrench held in the other hand. The top indicator will turn green when the cylinder is tightened correctly.
- 2 Check the top and bottom sealing 'O'-Rings on the operating head and replace if necessary. Before fitting the operating head onto the manifold, check that the UML PS Short valve is fitted. If fitting a new UML PS Short valve ensure it is only finger tight. Then place the operating head onto the manifold, so that the cylinder threaded opening is facing the cylinder elastic. (away from the bottom of the inflator).
- 3 Fit the retaining screw. This should be screwed in to place using a torque screwdriver set to 3.0 Nm. This will prevent damage to the operating head and ensure a good seal is maintained.


Fig 8.3 United Moulders Prosensor Automatic Operating Head



- 1 Take the automatic firing capsule and screw onto the operating mechanism in a clockwise direction. Screw right up ensuring there is no gap between the capsule and the base of the operating mechanism. Do up hand tight. The bottom indicator will turn green when the capsule is tightened correctly. Make a note of the batch number and manufacture date on the service record sheet.
- 2 Check that the cylinder sealing O-Ring in the end of the operating head has been correctly fitted, or replaced if necessary. Ensure that the cylinder has been check weighed before fitting to the lifejacket. Fit the gas cylinder to the firing mechanism using the torque wrench (4Nm) and head adaptor from the tool kit. The cylinder is gripped in one hand and the head tightened using the torque wrench held in the other hand. The top indicator will turn green when the cylinder is tightened correctly.
- 3 Check the top and bottom sealing 'O'-Rings on the operating head and replace if necessary. Before fitting the operating head onto the manifold, check that the UML PS Short valve is fitted. If fitting a new UML PS Short valve ensure it is only finger tight. Then place the operating head onto the manifold, so that the cylinder threaded opening is facing the cylinder elastic. (away from the bottom of the inflator).
- 4 Fit the retaining screw. This should be screwed in to place using a torque screwdriver set to 3.0 Nm. This will prevent damage to the operating head and ensure a good seal is maintained.


Fig 8.4 Hammar Operating Head

Fig. 8.4.1




Check that the indicator is green. Insert new inflator body with gas cylinder pointing upward inside the lifejacket (PFD). Let the sealing ring rest on the inflator body around the four lugs.

Fig. 8.4.2




Now check the new manual/ automatic cap as follows:
 1. Single point indicator showing green?
 2. Expiry date OK?
 If YES is the answer to both these questions, then proceed as follows.
 If NO get a new cap.

Fig. 8.4.3




Hold the gas cylinder through the fabric of the lifejacket.

Fig. 8.4.4




Position the replacement cap with the water inlet valve pointing to the right (7b) and press it FIRMLY onto the inflator body and sealing ring.

Fig. 8.4.5




While pressing FIRMLY onto the inflator body turn the BLACK locking ring clockwise into the locked position. Pull on the cap to make sure it has locked onto the inflator body.




Check that the black plastic handle is firmly attached to the Hammar cap.

Fig 8.5 Repacking the Ergofit 190N CS, 190N OS and 190N Pro



REPACKING THE SPRAYHOOD



Lay hood out so top seam with velcro retainers lays flat and straight.

Gather tubing and excess visor up and secure with velcro retainers.

Concertina hood so it lays flat against edge of the chamber. Affix velcro tabs on webbing to velcro retainers on chamber. Ensure webbing puller lays over the chamber collar.

Fig 8.5 Repacking the Ergofit 190N CS, 190N OS and 190N Pro (cont.)







<p>1</p>  <p>Concertina bottom left side of Chamber. Ensure capsule lays on top of the fabric. Run the zip slider round to the left side of the jacket.</p>	<p>2</p>  <p>Fold outer left side of chamber over towards the centre. Take care not to tangle the pull cord.</p>
<p>3</p>  <p>Fold the inner edge of the chamber over towards the outside .</p>	<p>4</p>  <p>Roll the inner edge of the chamber over again so that the inflation mechanism is visible on top . Thread pull handle through button hole in cover and tuck excess cord inside fold of chamber to avoid tangling.</p>
<p>5</p>  <p>Fold chamber collar down as far as it will go.</p>	<p>6</p>  <p>Fold the top edge back to make a concertina with the hood laying on top.</p>

Fig 8.5 Repacking the Ergofit 190N CS, 190N OS and 190N Pro (cont.)










<p>7</p>  <p>Fold top corners of collar down. Tuck hood in, taking care not to tangle light cord or hood pull webbing.</p>	<p>8</p>  <p>Tuck chin support inside itself so there is a straight line from corner to corner.</p>
<p>9</p>  <p>Fold the bottom right edge of inflator up as far as it will go.</p>	<p>10</p>  <p>Fold outer edge over towards the centre as far as it will go.</p>
<p align="center">FINAL INSTRUCTIONS FOR 190N CS AND EARLY VERSIONS OF 190N OS</p> <div style="display: flex; justify-content: space-between;"> <div data-bbox="98 1527 454 1841"> <p>11</p>  </div> <div data-bbox="454 1527 794 1841"> <p>12</p>  </div> <div data-bbox="794 1527 1495 1841"> <p>13</p>  <p align="center">190N OS 190N CS</p> </div> </div> <p>Concertina inner right edge over to fit. Tuck everything inside cover and close cover using zip from the right side. Fixing velcro burst tabs as you go.</p> <p>Tuck zip ends inside cover so the bottom of the jacket looks neat. Ensure firing mechanism is visible through the window.</p>	

Fig 8.5 Repacking the Ergofit 190N CS, 190N OS and 190N Pro (cont.)

FINAL INSTRUCTIONS FOR 190N Pro AND LATER VERSIONS OF 190N OS




Concertina inner right edge over to fit.
Tuck everything inside cover and close cover using zip from the left side. Fixing velcro burst tabs as you go.


Tuck zip ends inside cover so the bottom of the jacket looks neat. Ensure Firing mechanism is visible through the window.

Fig 8.6 Repacking the Ergofit 290N OC


Ensure hood webbing puller is placed above chamber collar, and velcro tabs are secured.



Fix light activator to its elastic retainer at the back of the collar.



Ensure pull cord handle is located in its garage on outer cover.




Ensure firing mechanism is armed correctly and green indicators are showing.

Lifting beackets should be fastened to the press studs on the chamber.

Epirb attachment.

REPACKING THE SPRAYHOOD



Lay hood out so tubing lays flat and straight against the back of the chamber.



Gather tubing and excess visor up and secure with velcro retainers.



Affix velcro tabs on webbing to velcro retainers on chamber. Ensure webbing puller lays over the chamber collar.

Fig 8.6 Repacking the Ergofit 290N OC (cont.)







<p>7</p>  <p>Fold top corners of collar down. Tuck hood in taking care not to tangle light cord or hood pull webbing.</p>	<p>8</p>  <p>Concertina bottom edge of chamber. Firing capsule should lie on top.</p>
<p>9</p>  <p>Fold outer edge of chamber in towards the centre.</p>	<p>10</p>  <p>Fold inner edge over as far as it will go.</p>
<p>11</p>  <p>Roll excess back on its self so the firing mechanism is on top. Thread pull handle through button hole in cover and tuck excess cord inside fold of chamber to avoid tangling.</p>	<p>12</p>  <p>Tuck everything inside cover and close cover using zip from the right side, fixing velcro burst tabs as you go.</p>

Fig 8.6 Repacking the Ergofit 290N OC (cont.)

<p>1</p>  <p>Fold up bottom right side of Chamber.</p>	<p>2</p>  <p>Fold outer right side of Chamber over towards the centre.</p>
<p>3</p>  <p>Fold the inner edge of the Chamber over towards the outside.</p>	 <p>Fold back chin support and roll underneath folded chamber.</p>
<p>5</p>  <p>Fold over excess chamber bringing light to the top.</p>	<p>6</p>  <p>Concertina the collar with two folds. The hood should lay on top.</p>

Fig 8.6 Repacking the Ergofit 290N OC (cont.)

13

Tuck hood in by curling the tubing inwards. care not to tangle light cord or hood pull webbing.

14

Tuck zip ends inside cover so the bottom of the jacket looks neat. Ensure Firing mechanism is visible through the window.

The final Packing Instructions shown above are for the earlier versions of the Ergofit 290N OC. Final Packing Instructions for later versions are given below.

12

Tuck everything inside cover and close cover using zip from the left side. Fixing velcro burst tabs as you go.

13


Tuck hood in by curling the tubing inwards. care not to tangle light cord or hood pull webbing.

14


Tuck zip ends inside cover so the bottom of the jacket looks neat. Ensure Firing mechanism is visible through the window.

Fig 8.7 Repacking the Ergofit 290N EX


Ensure hood webbing puller is placed above chamber collar, and velcro tabs are secured.



Fix light activator to its elastic retainer at the back of the collar.



Ensure pull cord handle is located in its garage on outer cover.




Ensure firing mechanism is armed correctly and green indicators are showing.

Lifting beackets should be fastened to the press studs on the chamber.

Epirb attachment.

REPACKING THE SPRAYHOOD



Lay hood out so tubing lays flat and straight against the back of the chamber.



Gather tubing and excess visor up and secure with velcro retainers.



Affix velcro tabs on webbing to velcro retainers on chamber. Ensure webbing puller lays over the chamber collar.

Fig 8.7 Repacking the Ergofit 290N EX (cont.)













<p>1</p>  <p>Concertina bottom left side of chamber. Ensure capsule lays on top of the fabric. On Hammar units, fold as shown.</p>	<p>2</p>  <p>Fold outer left side of Chamber over towards the centre. Take care not to tangle the pull cord of the firing head.</p>
<p>3</p>  <p>Fold the inner edge of the Chamber over towards the outside.</p>	<p>4</p>  <p>Roll the inner edge of the Chamber over again so that the inflation mechanism is visible on top. Ensure that the pull handle is through button hole in cover and located in its garage. Tuck excess cord inside fold of chamber to avoid tangling.</p>
<p>5</p>  <p>Bring cover over the completed left side, ensuring the inflation mechanism is visible through the window. Then concertina the collar with two folds. The hood should lay on top.</p>	<p>6</p>  <p>Fold top corners of collar down. Tuck hood in, taking care not to tangle light cord or hood pull webbing. Zip cover together secure the existing folds.</p>

Fig 8.7 Repacking the Ergofit 290N EX (cont.)

<p>7</p>  <p>Fold up bottom right side of Chamber.</p>	<p>8</p>  <p>Fold outer right side of Chamber over towards the centre. Release any build up of air using the oral inflation tube.</p>
<p>9</p>  <p>Fold the inner edge of the Chamber over towards the outside.</p>	<p>10</p>  <p>Fold back chin support and roll underneath folded chamber.</p>
<p>11</p>  <p>Fold over excess chamber bringing light to the top and zip up the rest of the cover. Ensure burst tabs are all secure.</p>	<p>12</p>  <p>Finally tuck zip ends inside cover so the bottom of the jacket looks neat. Ensure firing mechanism is still visible through the window.</p>

9.1 Parts List

Product Description	Part Number
60 gram CO ₂ Cylinder	12050
38 gram CO ₂ Cylinder	12045
United Moulders Mk5i Auto Capsule	10017
United Moulders Prosensor Manual Head with Grab Handle	
United Moulders Prosensor Auto Head with Grab Handle	
Operating Head Sealing O-Ring (Top and Bottom)	10373
Cylinder Sealing O-Ring	11048
Retaining Screw for Prosensor Heads	
Hammar Automatic Cap (MA1) with Grab Handle	11308
Hammar (MA1) Back Plate with 60gm CO ₂ Cylinder	11034
Hammar (MA1) Back Plate with 38gm CO ₂ Cylinder	12038
Hammar Release Key	11018
Whistle	10677
Whistle & Elastic Tube Attachment	12043
CSL Light	10226
Mouth Inflation Valve	10208
Mouth Inflation Valve Cap	10151
UML PS Short Valve	R17206
Venturi Vacuum System	10481
Servicing tool kit	10467
Cylinder adaptor for back pressure System	900032
Back pressure test unit	900031
Cylinder tightening tool	900030